



BOTTOM REINFORCEMENT

SUSPENDED SLAB PLAN 1:100

- 1. MINIMUM SLAB THICKNESS 257mm UNLESS NOTED OTHERWISE
- 2. WET AREAS SETDOWN 20mm FOR TILING & FALLS (HATCHED).
- DISTRIBUTION REINFORCEMENT, UNO: 172: N12 @ 300 UB 257: N12 @ 200 UB

----- INDICATES BOTTOM REINFORCEMENT

INDICATES LOAD BEARING BRICKWORK ========= INDICATES BRICKWORK ABOVE SLAB

FOR CONCRETE NOTES REFER TO COVER SHEET.

LB-LOWER BOTTOM REINFORCEMENT UB-UPPER BOTTOM REINFORCEMENT

8. FOR COLUMN SIZE REFER TO SHEET 1

COLUMN SHOWN UNDER UNLESS NOTED OTHERWISE.

9. BUILDERS NOTE: ENSURE SUSPENDED SLAB NOTCHING FOR ROOF RAFTERS IF REQUIRED.

(WHERE LOWER ROOF MEETS SUSPENDED SLAB.)

ADVANCED BUILDING ENGINEERS PTY LTI			
632 NEWCASTLE STREET, LEEDERVILLE, WA 6007. T. 08 9228 4644, F. 08 9328 2937 www.abewa.com.au			
DRAWING TITLE SUSPENDED SLAB PLAN - BOTTOM REINFORCEMENT	DRAWN	SCALE: 1:100	SHEET
	DESIGNED		S4 REV
	CHECKED		