



ROOF PLAN 1:100

- ALL TIMBER BEAMS TO BE LVL E-BEAM
- TD - R10 ROD FIX TO ROOF BEAM AND 200SQx10PL BASE PLATE ANCHORED INTO BRICKWORK 12c MIN BELOW BEAM. OR FULLY WELD TO Lintel.
- FOR ROOF NOTES REFER TO COVER SHEET
- COLUMN SHOWN AS UNDER UNLESS NOTED OTHERWISE.

TYPICAL BEAM CONNECTION NOTE:

- A) TIMBER TO TIMBER BEAM CONNECTION - PROVIDE EX8PL ANGLE CLEAT AND FIX TO EACH BEAM VIA 2M12BOLTS
- B) STEEL TO TIMBER BEAM CONNECTION - WELD EX10PL CLEAT TO STEEL BEAM AND FIX TO INTERSECTING BEAM VIA 2M12BOLTS.
- C) STEEL TO STEEL BEAM CONNECTION - WELD EX10PL CLEAT TO STEEL BEAM AND FIX TO INTERSECTING BEAM VIA 2M16BOLTS.

CONVENTIONAL ROOF FRAMING AND ROOF ANCHORAGE TO BE IN ACCORDANCE WITH BCA & AS 1684-SAA LIGHT TIMBER FRAMING CODE. (TYPICAL)

**UNIT 4
TILED ROOF**

**UNIT 1
METAL ROOF**

**UNIT 2
TILED ROOF**

**UNIT 3
METAL ROOF**



ADVANCED BUILDING ENGINEERS PTY LTD

632 NEWCASTLE STREET, LEEDERVILLE, WA 6007.
T. 08 9228 4644, F. 08 9328 2937 www.abewa.com.au

Robert David
MIE Aust CPEng
Chartered Professional Engineer
Membership No. 205080
The Institution of Engineers, Australia

DRAWING TITLE
ROOF PLAN

PROJECT		APPROVED BY:		SHEET
DRAWN				S3
DESIGNED		SCALE: 1:100		REV
CHECKED				-